



## EXXSOL D GRADE DEAROMATISED HYDROCARBONS

Our Exxsol D-Series products from ExxonMobil Chemical offer users a wide selection of dearomatised hydrocarbon fluids, with a typical Aromatic content below 1%. These fluids maintain good solvency characteristics for many applications. Because of their relatively high OELs, they often serve as replacements for more conventional solvents that might not meet health or environmental regulations. Heavier Exxsol D grades have boiling ranges between 140° and 310° C.

	Exxsol D30	Exxsol D155/170	Exxsol D40	Exxsol D180/200 SP	Exxsol D60	Exxsol D80	Exxsol D220/240	Exxsol D100	Exxsol D100S	Exxsol D120	Exxsol D140
Alternate Name	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
CAS No	N/A	N/A	N/A	64742-48-9	64742-48-9	64742-47-8	64742-47-8	64742-47-8	64742-47-8	64742-47-8	64742-46-7
Distillation Range (°C)	143 – 165	160 – 174	160 – 190	188 – 202	187 – 216	205 – 237	224 – 252	240 – 267	240 – 266	263 – 297	285 – 318
Flash Point (°C)	29	41	42	63	63	76	90	102	102	120	138
Aromatic Content (wt %)	0.001	0.006	0.003	0.03	0.06	0.06	0.2	0.4	0.07	0.6	1.0
Aniline Point (°C)	64	66	67	69	70	76	76	78	78	83	88
Density (@ 15°C)	0.762	0.771	0.775	0.789	0.792	0.804	0.810	0.817	0.816	0.828	0.834
Evap Rate (nButAc=100)	44	21	14	4.9	3.4	<1	<1	<1	<1	<1	<1

For further information, or to check for country availability, please contact your local Multisol Representative.

**Multisol Limited**  
 Huntsman Drive,  
 Northbank Industrial Park, Irlam,  
 Greater Manchester, M44 5EG

**Main:** +44 (0)161 775 1622  
**Fax:** +44 (0)161 777 9345  
**Email:** sales@multisolgroup.com  
**Web:** www.multisolgroup.com



Integrated Management System  
 PAS 99 IMR 510423  
 ISO 9001  
 ISO 14001  
 OHSAS 18001