



ISOPAR™ SERIES ISOPARAFFINIC HYDROCARBONS

Isopar is the brandname for our range of isoparaffinic fluids. Isopar fluids are manufactured under special conditions to ensure batch-to-batch uniformity and to eliminate unwanted impurities, such as aromatics, unsaturated olefins and reactive polar compounds. The high degree of purity, combined with the relative inertness of the saturated isoparaffinic structure, minimizes or eliminates adverse reactions in industrial processes and consumer applications.

	Isopar C	Isopar E	Isopar G	Isopar H	Isopar J	Isopar K	Isopar L	Isopar M	Isopar N	Isopar P	Isopar V
Alternate Name	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
CAS No	N/A	N/A	90622-57-4	90622-57-4	90622-57-4 90622-58-5	90622-57-4 90622-58-5	90622-58-5	64742-47-8	64742-47-8	64742-47-8	64742-46-7
Distillation Range (°C)	99 – 104	113 – 139	161 – 173	182 – 192	185 – 204	183 – 200	191 – 211	207 – 253	219 – 258	239 – 269	266 – 313
Flash Point (°C)	<0	6	42	58	63	60	64	78	87	103	124
Aromatic Content (wt %)	0.0002	0.0003	0.002	0.003	0.003	0.003	0.004	0.01	0.013	0.02	0.1
Aniline Point (°C)	78	72	77	80	80	80	81	83	85	86	97
Density @ 15°C	0.699	0.723	0.748	0.762	0.764	0.763	0.768	0.791	0.796	0.807	0.819
Evap Rate (nButAc=100)	368	159	24	7.5	5.5	6.0	4.5	<1	<1	<1	<1

For further information, or to check for country availability, please contact your local Multisol Representative.

Multisol Limited
Huntsman Drive,
Northbank Industrial Park, Irlam,
Greater Manchester, M44 5EG

Main: +44 (0)161 775 1622
Fax: +44 (0)161 777 9345
Email: sales@multisolgroup.com
Web: www.multisolgroup.com



Integrated Management System
PAS 99 (MR) 510423
ISO 9001
ISO 14001
OHSAS 18001