



SOLVESSO™ SERIES AROMATIC HYDROCARBONS

Our Solvesso Series of high aromatics offer high solvency and controlled evaporation characteristics that make them excellent for use in many industrial applications such as additives, paint and coatings, pesticides, industrial cleaning, mastics and sealants and process fluids. They are available in three boiling ranges with varying volatility. There are also naphthalene reduced and ultra-low naphthalene grades available. All Solvesso grades are products of ExxonMobil Chemical.

	Solvesso 100	Solvesso 100S	Solvesso 150	Solvesso 150ND	Solvesso 200	Solvesso 200ND
Alternate Name	N/A	N/A	N/A	N/A	N/A	N/A
CAS No	64742-95-6	N/A	64742-94-5	64742-94-5	64742-94-5	64742-94-5
Distillation Range (°C)	165 – 180	155 – 181	182 – 207	183 – 194	232 – 287	248 – 295
Flash Point (°C)	50	50	64	64	101	107
Aromatic Content (wt %)	>99	>99	>99	>99	>99	>99
Aniline Point (°C)	14	14	15	16	15	12
Density @ 15°C	0.878	0.878	0.900	0.886	0.987	0.993
Evap Rate (nButAc=100)	19	19	5.3	7.0	<1	<1

For further information, or to check for country availability, please contact your local Multisol Representative.

Multisol Limited
Huntsman Drive,
Northbank Industrial Park, Irlam,
Greater Manchester, M44 5EG

Main: +44 (0)161 775 1622
Fax: +44 (0)161 777 9345
Email: sales@multisolgroup.com
Web: www.multisolgroup.com



Integrated Management System
PAS 99 IIR 510423
ISO 9001
ISO 14001
OHSAS 18001